

DUPLI-COLOR Flip Flop / Flip Flop Ultra Automotive

Ord.-no.: look at ordering information

Technical Information



Color change effect for individually creations. Depending on incidence of light and perspective of the spectator, the effect changes the colour. Specially impressive effect is achieved on a dark ground. Suitable for glass, ceramics, stone, metals, etc.

Quality & properties

- High-grade nitro-combi quality with a combination of special binders and pigments
- Good flow, smooth surface
- Quick-drying
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- Very efficient
- High degree of gloss
- Round spray jet, fine atomization
- Very smooth, level run
- Vampire: violet to green scarab: green to anthracite tropical: red to gold/brown ultra lagoon: violet to bordeaux red ultra lapis: azure blue to turquoise ultra sunrise: green brown to gold ultra miracle: silver chromaflair

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - ◊ green/violet
 - ◊ light red/dark red
 - ◊ light blue/dark blue
 - ◊ light green/dark green
 - ◊ light violet/dark violet
 - ◊ multicolor/silver
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency: 150 ML – 0.4 m²
- Dry to touch: 30 min
- Dust dry: 5 min
- Completely dry: 24 h
- Overcoatable: 1 h
- Surfaces: glass, ceramics, stone and metals
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 150 ML

How to use

- The ground has to be clean, dry and free from fat.
- Mask off areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray several thin coats from a distance of approx. 25 cm.
- Let lift off for 5 minutes after every cross coat.
- The effect as shown on the cap will be achieved with 3 - 4 cross coats.
- To increase the gloss and weather-resistance, we recommend to apply a top coat of acrylic clear lacquer.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com