

DUPLI-COLOR TUNING SPRAYPAINT PEARL WHITE

Ord.-no.: 133312



Technical Information

Gives a satin pearl shine especially to white, but also to coloured surfaces.

Quality & properties

- High-grade nitro-combi quality with pearleffect pigments
- Very efficient
- Excellent adhesion
- Suitable for painting and repairing objects for indoors and outdoors use
- Weather-resistant, light-proof, UV-resistant
- Good flow, smooth surface
- Quick-drying
- Scratch-, shock- and impact-resistant

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: white
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency: 150 ML – 0.8 m²
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 2 h
- Surfaces: objects for indoors and outdoors
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 150 ML

How to use

- Mask off areas not to be painted.
- Prepare the surface: remove rust and dirt. The ground has to be clean, dry and fat-free. Apply a covering layer with a DUPLI-COLOR Acrylic lacquer (e.g.. Tuning Spray Paint RAL). Observe the instructions on the can. Let dry for approx. 1 hour.
- Before use, shake the can with the Pearl Effect Lacquer for approx. 3 minutes.
- Spray from a distance of 25 cm in 30 minute intervals 2 - 3 thin coats till the desired effect is achieved.
- Do not spray over synthetic paints!
- In case spray mist has been produced, this can be polished off after 48 hours with presto Polishing Paste.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.