

DUPLI-COLOR EFFECT PRIMER

Ord.-no.: look at ordering information

Technical Information



The optimal ground for phantastic special effects: white matt for e.G. DUPLI-COLOR NEON SPRAY. Black glossy for e.G. DUPLI-COLOR GLITTER SPRAY. Suitable for metals, glass, ceramics, stone and many other surfaces.

Quality & properties

- High-grade nitro-combi quality
- Very good coverage
- Highly efficient
- Excellent adhesion
- Quick-drying
- Good flow, smooth surface
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - ◊ white
 - ◊ black
- Smell: Characteristic
- Degree of gloss:
 - ◊ mat, 10 ±2 GU
 - ◊ gloss, >75 GU
- Efficiency:
 - ◊ 400 ML – 0.8 - 1.5 m²
 - ◊ 150 ML – 0.3 - 0.6 m²
- Dry to touch: 30 min
- Overcoatable: 1 h
- Surfaces: metals, glass, ceramics, stone and many other surfaces
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 8300/20 bar
 - ◊ 4000/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML

How to use

- Remove rust and dirt.
- The ground has to be clean, dry and free from fat.
- Cover areas not to be painted.
- Before use, shake can for 2 -3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of 25 cm several thin coats.
- Coatable with acrylic- oder synthetic lacquers.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline

1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com