

DUPLI-COLOR Wood Preservation Spray

Ord.-no.: look at ordering information

Technical Information



Solvent-based, open-pored, breathable and waterproof thin layer glaze. It is a permanent all-weather protection and improves wood in the indoor and outdoor area. Well suitable for all kinds of wood: fences, pergolas, garden sheds, carports, gates, windows etc.

Quality & properties

- 2-in-1: Primer and glaze
- Suitable for all kinds of wood (if appropriate application is provided)
- Natural breathing of wood is maintained
- Individually adjustable spray direction
- Permanent all-weather protection
- Open-pored and breathable
- Waterproof, UV-resistant
- Doesn't contain any wax
- High efficiency: up to 4 m² / can 500ml
- Long-term protection up to 3 years (depending on construction, weather conditions and appropriate treatment)

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ walnut dark
 - ◊ pine
 - ◊ teak
 - ◊ rosewood
 - ◊ walnut light
 - ◊ transparent
- Smell: Characteristic
- Efficiency: 500 ML – 2 - 4 m²
- Dry to touch: 4 - 6 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: fences, pergolas, garden sheds, carports, gates, windows etc.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 500 ML

How to use

- Ambient temperature 15-25°C.
- Surfaces need to be stable, clean, solid, dry, free of grease, wax and closed coating films
- Grind away weathered wooden parts and grind old varnishes
- Transparent varnish is not suited as a sole painting for outside
- Shake can for 2 minutes and test spray
- Optimal spray distance: approx. 25 cm
- Apply at least two cross-coats
- Number of coats has influence on the colour shade - each coat makes the colour shade darker
- At painting of pannellings we recommend protection of wood from both sides
- Do not coat with acrylic lacquer. Attention: Spray mist develops.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 19, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com