

# DUPLI-COLOR SPOTMARKER FOR CONSTRUCTION

Ord.-no.: look at ordering information

## Technical Information



Spotmarker for Construction and Forestry – Upside-down application. NEW: patented security cap with lockable spray actuator. Prevents from unintended spraying. Special spray paint for markings with overhead-valve. Ideal for markings on building sites, roadworks, structural and civil engineering. High covering and intensive shining. Optional possible to apply with Markingroller or -gun. For temporary markings.

### Quality & properties

- Innovative one-hand safety cap with spray trigger lock prevents unintentional spraying - now with Easy-touch release Cap acceptable for special applications (for use in accessories)
- Special tilt valve for accurate wall and floor marking
- Outstanding adhesion also to wet surfaces
- Markings remain strongly visible from 6 to 9 months
- High coverage quality ensures high yield
- Intensive luminosity of the fluorescent hues
- Also easy to apply with gloves
- Clean, drip-free marking
- Environmentally friendly and non-hazardous to health
- Self-cleaning system, can be 100% emptied by spraying --> no venting required

### Physical & chemical data

- Base: Acrylic resin
- Colourname:
  - ◊ blue
  - ◊ red
  - ◊ yellow
  - ◊ white
  - ◊ orange
  - ◊ green
  - ◊ pink
- Efficiency: 500 ML – 140 m
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 500 ML

### How to use

- After you hear the sound of the balls inside the can, vigorously shake the can for one more minute.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 19, 2022 – This release replaces all eventually earlier issued versions.

