

DUPLI-COLOR MAGNETIC PAINT

Ord.-no.: look at ordering information

Technical Information



MAGNETIC PAINT is a water-based interior paint, which is suitable to affix magnets. It offers a lot of applications in the most different fields and can even be used on concave surfaces. And the best: MAGNETIC PAINT can be coated, so you can easily adapt the color to the surrounding wall. For painting on latex paint, wood, wallpaper and other materials.

Quality & properties

- High-grade acrylic dispersion, containing iron pigments
- Water-based
- Excellent adhesion and coverage
- For indoor applications
- Even for use on concave surfaces
- Re-coatable with dispersion
- Can be repapered with a light wallpaper

Physical & chemical data

- Base: acrylate dispersion
- Colourname:
 - ◊ grey
 - ◊ light grey
- Smell: Neutral
- Efficiency: 1,00 L – 2 - 3 m²
- Dry to touch: 3 h
- Overcoatable: 6 h
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- pH-Value: 8
- Storage stability: 1 y
- Content:
 - ◊ 2,50 L
 - ◊ 500 ML
 - ◊ 1,00 L
 - ◊ 4,00 L

How to use

- The ground should be smooth and absolutely dry.
- Cover surrounding area carefully to protect it from paint splatters.
- Completely remove wallpapers, which do not perfectly adhere to the wall.
- Extremely absorbent surfaces should be pretreated with a dispersion primer.
- To improve adherence, smooth, lacquered surfaces (e.g. doors) should be sanded before.
- Magnetic Paint is not suitable for outdoor applications. Do not use on objects which are exposed to humidity.
- Stir up well before application. This is in order to spread the metal pigments in the paint evenly.
- Do not mix the Magnetic Paint with any other paint or with water.
- Carefully imbue the short-hair paint roller, as you are used from other latex paints, and apply the first coat. Let the first coat dry for 3 – 4 hours. Then apply the 2nd coat of Magnetic Paint. At a coat thickness of 100 µm (2-3 coats) the magnetic effect is sufficient for customary magnets.
- To increase the magnetic effect, the surface can be painted in several coats, or use our super magnets. As soon as the coating is dry to touch (at least 6 hours), the Magnetic Paint can be coated with any latex paint in any colour or repapered with a thin wallpaper.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 19, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com