

DUPLI-COLOR AQUA LACK

Ord.-no.: look at ordering information



Technical Information

For environment-conscious spraying in a quick-drying, waterbased acrylic quality. With a good coverage. You determine the colour depth from translucent to opaque. Weather-resistant after curing, suited for polystyrene. A special spray technology reduced spraydust. Vanilla smell instead of annoying solvent odour - 90 % of the solvents were replaced by water. These properties allow to spray even in interior rooms. Acc. to DIN EN 71-3 suitable for the painting of toys.

Quality & properties

- High-quality acrylic lacquer, waterbased
- Less spray mist, therefore pleasant usage even indoor
- Suitable for polystyrene
- Eco friendly
- Waterbased
- Suitable for toys

Physical & chemical data

- Base: Waterbased acrylic resin
- Colouname:
 - ◊ traffic yellow
 - ◊ pastel orange
 - ◊ telemagenta
 - ◊ anthracite grey
 - ◊ ice blue
 - ◊ spring green
 - ◊ terracotta
 - ◊ colza yellow
 - ◊ vermillion
 - ◊ gentian blue
 - ◊ light blue
 - ◊ yellow green
 - ◊ silver grey
 - ◊ chocolate brown
 - ◊ cream
 - ◊ beige
 - ◊ brown black
 - ◊ mole brown
 - ◊ mittelgelb
 - ◊ orange
 - ◊ scharlachrot
 - ◊ karminrot
 - ◊ rosa
 - ◊ ultramarine blue
 - ◊ light turquoise
 - ◊ may green
 - ◊ grey
 - ◊ dark grey
 - ◊ anthracit
 - ◊ white
 - ◊ broken white
 - ◊ black
 - ◊ pistachio green
 - ◊ jet black
 - ◊ flame red
 - ◊ silver
 - ◊ gold
- Smell: Vanilla
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ semi mat, 25 ±5 GU
- Efficiency: 150 ML – 0.8 - 1.2 m²
- Dry to touch: 2 h
- Dust dry: 15 - 20 min

- Completely dry: 24 h
 - Surfaces: wickerware, wood, carton, metal, fabric, paintable hardplastics, glass, ceramics, polystyrene
 - Minimum Working Temperature: 10 °C
 - Maximum Working Temperature: 25 °C
 - Vapour pressure: 4000/20 bar
 - Storage stability: 4 y
 - Content:
 - ◊ 350 ML
 - ◊ 150 ML
-

How to use

- The surface must be clean, absolutely fat-free and dry. Remove loose parts. In spite of low formation of spray mist, we recommend to protect the surrounding area. Pre-paint absorbent grounds with AQUA Primer. Let dry (at least 2 hours). Prime hardplastics with a Plastic Primer.
- Shake can for 3 minutes, test spray. The optimal distance is approx. 25 cm. Spray in 2 minute intervals several thin layers. AQUA spray paint should not be applied during temperatures lower than 15°C, as this might delay drying time.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com