

DUPLI-COLOR TUNING SPRAY PAINT

Ord.-no.: look at ordering information



Technical Information

The powerful basic colors for all cases: for spraying and brushing. Fast drying paints for styling paints, contrast and Laminating paints on the vehicle.

Quality & properties

- High-grade nitro-combi quality
- Very good colour-matching
- Very good coverage
- Durable gloss, Very good colour retention: weather-resistant, light-proof, UV-resistant
- Excellent adhesion
- High surface hardness and good elasticity, Scratch-, shock- and impact-resistant
- Good flow, smooth surface, Polishable, dirt-resistant surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Limited resistance against petrol

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - ◊ black
 - ◊ white
- Smell: Characteristic
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ semi mat, 25 ±5 GU
- Efficiency:
 - ◊ 12 ML – small spots m²
 - ◊ 150 ML – 0.5 m²
 - ◊ 400 ML – 1.3 m²
- Dry to touch: 50 min
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 30 min
- Surfaces:
 - ◊ Suitable for indoors and outdoors applications
 - ◊ metals, glass, ceramics, stone and many other surfaces
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 13/20 bar
 - ◊ 4000/20 bar
- Flash point: 27 °C
- Storage stability: 10 y
- Content:
 - ◊ 12 ML
 - ◊ 150 ML
 - ◊ 400 ML

How to use

- Clean underground from dirt, fat and rust. If necessary, treat existing pore rust with presto Rust Stop.
- Fill and sand uneven surfaces.
- Apply a primer, e.g. DUPLI-COLOR Primer art.no. 191268! To improve adhesion, pre-treat plastic parts with DUPLI-COLOR Plastic Primer art.no. 327292.
- The surface has to be clean, dry and free from fat.
- Before use, shake the can vigorously for 3 minutes.
- Test spray to check colour-matching.
- The spray distance should be approx. 20-30 cm.
- Spray several thin cross-coats in 3 - 5 minute intervals.
- Do not spray over synthetic paints

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com