

## DUPLI-COLOR HAMMERFINISH

Ord.-no.: look at ordering information

### Technical Information



For metallic shining surfaces with distinctive hammerfinish effect. Also to cover up small unevennesses on surfaces of metal, stone, glass, coatable plastics etc. Suitable for inside and outside use. Quick-drying nitro combi quality.

### Quality & properties

- High-grade nitro-combi quality
- Very good coverage: hides small surface unevennesses due to distinct hammer finish effect
- Excellent adhesion on many surfaces
- Quick-drying
- Suitable for finishing and repair of indoors and outdoors objects.
- Resistant to diluted cleansers
- High resistance to light, weather and water
- Scratch-, shock- and impact-resistant

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - ◊ blue
  - ◊ silver
  - ◊ copper
  - ◊ green
  - ◊ gold
  - ◊ anthracite
- Smell: Characteristic
- Efficiency: 400 ML – 0.8 m<sup>2</sup>
- Dust dry: 5 min
- Completely dry: 60 min
- Surfaces: metal, glass, stone and coatable hard plastics etc.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Remove residues of old paintings and rust.
- Slightly sand and prime if necessary.
- Mask off areas not to be painted.
- The surface has to be clean, dry and fat-free.
- Before use, shake can for 3 minutes.
- Test colour of spray and compatibility of the lacquer at an invisible spot.
- Spray a thin coat from a distance of approx. 25 cm. Then repeat to spray one or two more thin layers in 1 minute intervals.
- Do not spray over synthetic paints!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)