

DUPLI-COLOR Alkyton Repair Sprays Ral Colors, Spezial Colors

Ord.-no.: look at ordering information



Technical Information

Quality lacquer in high-grade synthetic quality. Due to the possibility to repair scratches and paint damages on painted surfaces quickly and efficiently, this paint prevents the formation of damages by corrosion. Ideal to repair damages which arose during assembly and maintenance, but also for special applications on difficult to reach spots, e.g. in niches or on handrails.

Quality & properties

- High-grade synthetic lacquer
- Quick-drying
- Suitable to repair indoors and outdoors objects
- With especially good coverage and filling power
- Avoids the formation of corrosion
- Durable colour retention
- Very resistant to weathering, light-proof, UV-resistant
- Very good flow for smooth surfaces
- Excellent adhesion

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ traffic red
 - ◊ moss green
 - ◊ iron grey
 - ◊ jet black
 - ◊ white aluminium
 - ◊ pure white
 - ◊ silver
 - ◊ black anthracite
 - ◊ copper
- Smell: Characteristic
- Degree of gloss:
 - ◊ high gloss, >85 GU
 - ◊ mat, 10 ±2 GU
- Efficiency: 150 ML – 0.5 - 0.8 m²
- Dry to touch: 4 h
- Dust dry: 30 min
- Completely dry: 24 min
- Overcoatable: 24 h
- Surfaces:
 - ◊ grate (derust manually), steel, primer, wood and well-adhering old paintings. For indoor and outdoor applications
 - ◊ grate (derust manually), steel, primer, wood and well-adhering old paintings. For indoor and outdoor applications
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 35 °C
- Vapour pressure:
 - ◊ 8300/20 bar
 - ◊ 2100/20 bar
- Storage stability: 10 y
- Content: 150 ML

How to use

- The surface has to be clean, dry and fat-free.
- Remove loose parts of old paint and rust, then slightly sand and prime.
- Let dry for 1 – 2 hours.
- Mask off areas not to be painted.
- Before use, shake can for 2 – 3 minutes.
- Test colour and compatibility of the lacquer at an inconspicuous spot.
- Spray from a distance of approx. 25 cm.
- Spray several thin coats in 2 minute intervals. Shake can from time to time to avoid sedimentation of the

- special pigments in the paint. This might cause colour divergences.
- Coatable within 2 hours or after 24 hours.
- Do not coat with acrylic paints, not even after curing!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com