

DUPLI-COLOR TUNING ALU WHEEL PAINT

Ord.-no.: look at ordering information



Technical Information

For lacquering and repair works in the most current aluminium shades, especially for alloy rims.

Quality & properties

- High-grade, quick-drying nitro-combi paint
- Good flow, smooth surface
- Weather-resistant, light-proof, UV-resistant (non-yellowing)
- Limited fuel-resistance
- Good colour- and gloss retention
- Hard surface, abrasion-resistant

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - ◊ viper
 - ◊ argento
 - ◊ arctic
 - ◊ quartz
- Smell: Characteristic
- Degree of gloss:
 - ◊ semi gloss, 45 ±5 GU
 - ◊ semi mat, 25 ±5 GU
- Efficiency:
 - ◊ 150 ML – 0.5 m²
 - ◊ 12 ML – small spots m²
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 30 min
- Surfaces: aluminium shades
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 8300/20 bar
 - ◊ 58/20 bar
- Flash point: 27 °C
- Storage stability: 10 y
- Content:
 - ◊ 150 ML
 - ◊ 12 ML

How to use

- Carefully clean rims from dirt, fat and brake-dust. Treat existing pore rust with presto Deruster.
- The ground has to be sanded, clean, dry and fat-free.
- Mask off the rim edges with masking tape. Use paper to protect surrounding area from spray-dust.
- Prime with DUPLI-COLOR Primer. After drying, slightly sand (sanding paper grain P600)
- Before use, shake the can vigorously for 3 minutes.
- Test spray to check colour-matching.
- Spray several thin coats in 3 - 5 minute intervals from a distance of approx. 25 cm.
- After 30 minutes drying time, coat with DUPLI-COLOR TUNING WHEEL PAINT Clear Coat to protect the metal pigments in the lacquer.
- Do not spray over synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com