

# DUPLI-COLOR TUNING TRANSPARENT REMOVER

Ord.-no.: 721434



## Technical Information

With DUPLI-COLOR Transparent Remover paintings of Transparent-Spray can be removed easily from the painted objects.

### Quality & properties

- Highly dissolving properties
- User-friendly

### Physical & chemical data

- Base: Special combination
- Colourname: transparent
- Smell: Characteristic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Flash point: n.a.
- Storage stability: 10 y
- Content: 150 ML

### How to use

- Shake can before use.
- Spray from a distance of approx. 10 - 15 cm.
- Test spray at an invisible spot.
- Carefully cover painted areas.
- Then apply the Transparent Remover generously.
- Remove the lacquer with a dry, lint-free cloth.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 19, 2022** – This release replaces all eventually earlier issued versions.