

DUPLI-COLOR COLOR SPRAY CLEAR COAT

Ord.-no.: look at ordering information



Technical Information

Synthetic paint high gloss, satin matt and matt colours, clear coat and prime for all handicraft and DIY works on wood, metal, aluminium, glass, stone, carton, paper, eternite, porcelain and many coatable plastics.

Quality & properties

- High-grade synthetic quality
- Fast-drying
- Suitable for indoors and outdoors applications
- Good coverage and filling power
- Good colour and gloss retention
- Resistant to weathering, light-proof, UV-resistant
- Excellent flow for even surfaces
- Good adhesion on nearly all surfaces
- Scratch-, bump- and impact-proof

Physical & chemical data

- Base: Alkyd resin
- Colourname: transparent
- Smell: Characteristic
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ mat, 10 ±2 GU
- Efficiency:
 - ◊ 400 ML – 0.8 - 1.2 m²
 - ◊ 150 ML – 0.3 - 0.45 m²
 - ◊ 600 ML – 1.2 - 1.8 m²
 - ◊ 200 ML – 0.4 -0.6 m²
- Dust dry: 30 min
- Completely dry: 24 h
- Overcoatable: 2 h
- Surfaces: wood, metal, aluminium, glass, stone, carton, paper, eternite, porcelain and many coatable plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 8300/20 bar
 - ◊ 23/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML
 - ◊ 600 ML
 - ◊ 200 ML

How to use

- The ground has to be clean, dry and fat-free
- Remove loose flakes of old paints and de-rust, then sand and prime. Before painting plastic parts, use DUPLI-COLOR Plastic Primer. Let dry for 1 - 2 hours.
- Mask off surfaces not to be painted.
- Before use, shake can for 3 minutes.
- Test colour of spray and compatibility at an invisible spot.
- Spray distance: approx. 25 cm
- Spray several thin coats in approx. 2 minute intervals.
- Re-coatable within 2 hours or not earlier than after 24 hours.
- Do not coat with acrylic lacquer - not even after curing!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 19, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com