

## DUPLI-COLOR profi 1K Clear Coat

Ord.-no.: 478796, 478802

## Technical Information



DUPLI-COLOR 1K clear coat is a UV-resistant, fast-drying clear coat that can be applied universally at all existing base coats (solvent-based). Available in high gloss and satin gloss quality. Because of its very good flow and ease of applying good for the conservation and sealing of wood, wood composites, iron and steel for indoor and outdoor application.

### Quality & properties

- Fast drying time
- Easy application
- Can be used on all solvent-based paints
- UV resistant
- Good flow
- No yellowing
- For indoor and outdoor application

### Physical & chemical data

- Base: Acrylic resin
- Colourname: transparent
- Smell: Characteristic
- Degree of gloss:
  - ◊ high gloss, >85
  - ◊ semi gloss, 45 ±5 GU
- Efficiency: 400 ML – 1.5 - 2.0 m<sup>2</sup>
- Dry to touch: 2 h
- Dust dry: 10 min
- Completely dry: 24 h
- Surfaces: Solvent-based basecoats, wood, wood composites, iron and steel
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Solvent-based paints can be top-coated with 1 component clear coat once they have dried for 30 minutes
- Shake can for 2 minutes
- Carry out spray test
- Not suitable for recoating water-based paints
- Don't spray on synthetic resin areas!
- For an optimal coating result bring can to temperature prior to use (20 - 25 °C) and a relative air humidity of 45 - 60%. Please note: a high air humidity can cause loss of gloss.
- Dust-dry: 10min., dry to touch: 2h. Can be polished after: 24h. (20°C)
- Use an adequate respirator mask (we recommend type A2/P3)

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

