

DUPLI-COLOR ZINC PRIMER AUTOMOTIVE

Ord.-no.: 667022



Technical Information

Outstanding protection against corrosion for all iron metals, such as car bodies, exhaust systems, gates, machines, metal housings, metal fittings, fences etc. Especially suitable for the protection of welding seams and metals which are exposed to corrosion. Cathodic rust-protection on a very high technical level, which is very easy and quick to apply.

Quality & properties

- Very easy and quick to apply cathodic corrosion protection for blank metals
- High-grade zinc coating with more than 90 % zinc share in the dry film
- Resistant to highest demands against corrosion
- Ideal for all metals in outside places, which are liable to rust
- Highheat-resistant up to 600°C
- Particularly suitable for welding seams
- Good flow
- Coatable
- For colour-matching repair of zinc-plated objects use DUPLI-COLOR ZINC-ALU SPRAY

Physical & chemical data

- Base: Epoxy-ester
- Colourname: grey
- Smell: Characteristic
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1.0 - 1.5 m²
- Dry to touch: 20 min
- Surfaces: car bodies, exhaust systems, gates, machines, metal housings, metal fittings, fences etc.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Storage stability: 10 y
- Content: 400 ML

How to use

- The metal surface has to be blank and free from fat.
- Due to the high density, the Zinc Primer has to be shaken for at least 2 minutes after you hear the noise of the mixing-balls. Otherwise the valve could block.
- Shake the can vigorously for approx. 2 - 3 minutes.
- Test spray at an invisible spot.
- Apply several covering coats.
- Spray from a distance of approx. 25 - 30 cm.
- After drying (approx. 24 hours) apply primer and top coat.
- Do apply just thin coats to objects, which are exposed to high heat. If necessary, re-coat with temperature-resistant lacquer (test painting).
- Overpainting with other paints is not recommended.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

